

Permissible media:	R22, R134A, R404A, R407C, R507
Operating pressure:	0 - 30 bar
Life span:	min. 20 mio switchings
Ambient temperature:	-40 to +70°C
Media temperature:	-40 to +150°C
Material:	Brass, stainless steel, PTFE, EPDM
Magnetic capacity:	6 Watt at DC / 9VA at AC
Coil Connector:	DIN 43650 A - PG 11 (PG9)
Coil Protection:	IP65 with connector

Refrigerating

2/2-way

Solenoid Valves
 with soldering connection
 for tubes D 1/4" and 3/8"

Connection Tube-D	KV ¹⁾	Weight	Article Number (Solenoid valve incl. coil and connector)	
			normally closed	normally open

1/4"	0,3	0,20 kg	VAI50*	VAI53*
3/8"	0,4	0,24 kg	VAJ50*	VAJ53*



Series: VA50

1) The KV-Value is the water flow in m/h³,
 at pressure drop across the valve of 1 bar.

- * **Voltage code:** 0 = without coil
 1 = 230V 50/60 HZ
 2 = 024V DC
 3 = 024V 50/60 HZ
 4 = 012V DC

The voltage code is the end number of
 the valve article number. (e.g.: VAJ503)

FEATURES

- low noise switching
- high switching frequency
- compact design
- low energy consumption

Connection Tube-D	Nominal Refrigeration Capacity (KW) ²⁾											
	Liquid				Suction Steam				Hot Gas			
	R22	R404A R507	R134A	R407C	R22	R404A R507	R134A	R407C	R22	R404A R507	R134A	R407C
1/4"	6	4,17	5,6	5,7					2,8	2,3	2,2	2,94
3/8"	8	5,56	7,4	7,6					3,7	3,05	2,93	3,9

2)
 The nominal liquid and suction steam capacity is based on the evaporation temperature t_e = -10°C liquid temperature ahead the valve t_v = +25°C and Dp = 0,15 bar.

The nominal hot gas capacity is based on the liquefying temperature t_k = +40°C, pressure drop across the Valve Dp = 0,8 bar, hot gas t_h = +65°C and subcooling of refrigerant liquid D_{ts} = 4 K.