

**Permissible media:** R22, R134A, R404A, R407C, R507  
**Operating pressure:** 0,2 - 30 bar  
**Life span:** min. 5 mio. switchings (oiled media)  
**Ambient temperature:** -40 to +70°C  
**Media temperature:** -40 to +150°C  
**Material:** Brass, stainless steel, PTFE, EPDM  
**Magnetic capacity:** 10 Watt at DC / 18VA at AC  
**Coil Connector:** DIN 43650 A - PG 11 (PG9)  
**Coil Protection:** IP65 with connector

## Refrigerating

### 2/2-way Solenoid Valves with soldering connection for tubes D 1 1/8" - 1 5/8"

Connection Tube-D	KV <sup>1)</sup>	Weight	Article Number (Solenoid valve incl. coil and connector)	
			normally closed	normally open
1 1/8"	12	0,95 kg	<b>VDN01*</b>	<b>VDN04*</b>
1 3/8"	13	1,10 kg	<b>VDO01*</b>	<b>VDO04*</b>
1 5/8"	14	1,25 kg	<b>VDP01*</b>	<b>VDP04*</b>



## Series: VD01

<sup>1)</sup>The KV-Value is the water flow in m<sup>3</sup>/h , at pressure drop across the valve of 1 bar.

\*  
**Voltage code:** 0 = without coil  
 1 = 230V 50/60 HZ  
 2 = 024V DC  
 3 = 024V 50/60 HZ  
 4 = 012V DC

The voltage code is the end number of the valve article number. (e.g.: VDN013)

### FEATURES

- low noise switching
- high switching frequency
- compact design
- low energy consumption

Connection Tube-D	Nominal Refrigeration Capacity (KW) <sup>2)</sup>											
	Liquid				Suction Steam				Hot Gas			
	R22	R404A R507	R134A	R407C	R22	R404A R507	R134A	R407C	R22	R404A R507	R134A	R407C
1 1/8"	240	166,8	223,2	228	26,4	24	19,2	25,2	110,4	90,0	87,6	116,1
1 3/8"	260	180,7	241,8	247	28,6	26	20,8	27,3	119,6	97,5	94,9	125,7
1 5/8"	280	194,6	260,4	266	30,8	28	22,4	29,4	128,8	105,0	102,2	135,4

<sup>2)</sup> The nominal liquid and suction steam capacity is based on the evaporation temperature  $t_0 = -10^\circ\text{C}$  liquid temperature ahead the valve  $t_v = +25^\circ\text{C}$  and  $\Delta p = 0,15$  bar.

The nominal hot gas capacity is based on the liquefying temperature  $t_k = +40^\circ\text{C}$ , pressure drop across the Valve  $\Delta p = 0,8$  bar, hot gas  $t_h = +65^\circ\text{C}$  and subcooling of refrigerant liquid  $\Delta t_u = 4$  K.